

# LIGHT WEIGHT FILLER



## Description

Light weight ready mixed filler

## Intended use

- Filling holes and cracks of all sizes

## Product advantages

- + Excellent adhesion to substrates
- + Fills & finishes in a single pass
- + No thickness limitations
- + Very easy to sand
- + Does not shrink or crack
- + Very fine finish
- + Brillant white



## ENVIRONMENTAL DATA

### INDOOR AIR EMISSIONS

Information on the level of emissions of volatile substances into indoor air presenting a risk of toxicity by inhalation, on a class scale from A+ (very low emissions) to C (high emissions)



### COMPOSITION

**40** OF RAW MATERIALS  
% OF NATURAL ORIGIN

Water

### V.O.C CONTENT

VOC Directive 2004/42/EC: Cat A/a EU limit value: 30 g/L  
This product contains a maximum 0,5 g/L PAE

### PACKAGING

Contain at least 30% recycled plastic  
Not recyclable

### MANUFACTURING

This product is manufactured in our factory whose environmental management system is certified by Afnor



Beissier is committed to the sustainable development of its activities and has integrated CSR into its strategy our company has achieved an exemplary level on the "Engagé RSE label" assessment benchmark



# LIGHT WEIGHT FILLER

## USE

### DILUTION

Ready mixed

### APPLICATION

#### ▪ Conditions

Do not apply at temperatures of below + 5°C or above + 35°C, or at a relative humidity of above 80% H.R.

#### ▪ Equipment

Filling knife, blade

#### ▪ Equipment cleaning

With water before completely dry. Do not throw away into drains, dispose of this material and its container to an approved disposal contractor or taken to municipal collection point. Do not dispose into the environment.

### AVERAGE CONSUMPTION

1 L/m<sup>2</sup> per mm thickness  
(Depending on application thickness)

### SUBSTRATES

Concrete, cellular concrete, cement, concrete block, brick, plaster, plasterboard, previously printed wood, old painted substrates.

*Substrates must be hard, cohesive, clean, sound and dry according to the local standards.*

### OVERCOAT

Primer, filler, conventional paint, light-weight wall coverings

### WORKING TIME AT 20°C

Unlimited

### WAITING TIME BEFORE OVERCOATING

Once completely dry

## TECHNICAL DATA

### COMPONENTS

Polymer base aqueous phase coat mix, mineral fillers, additives.

### DENSITY

0,4 ± 0,05

### pH

8,5 ± 1

### COLOUR

White

### CLASSIFICATION

NF T 36-005 - Family IV, class 4b

### NORM

NF EN 16566

### HEALTH AND SAFETY



Use in a well-ventilated place. Avoid direct contact with skin and eyes. In case of prolonged contact, it is recommended to wear suitable gloves. Application by projection, wearing glasses and a mask is recommended. Safety data sheet available on [www.beissier.eu](http://www.beissier.eu) or [www.quickfds.com](http://www.quickfds.com)

### PACK SIZES

750 ml bucket

### STORAGE

12 months from date of manufacture, in unopened original packaging, protected from frost, heat (max. +30°C), sun and moisture. Close well after use. Store in original packaging.

This data sheet supersedes and replaces any prior sheet relating to the same product. Date of issue : **July 2025**

The purpose of this data sheet is to inform our customers about our product's properties. The information presented in the sheet is based on the current state of our knowledge. However, this information is no substitute for a description pertaining specifically to the type and condition of the substrate concerned. Since technical progress is continuously being made, it is our customer's responsibility, prior to use, to check with us that updated edition of this sheet has not been issued.

